

COPPER GASKET SEALER

Spanjaard Copper Gasket Sealer is an adhesive gasket-sealing and positioning spray containing conductive copper powder that takes up surface irregularities. Suitable for use on a wide variety of gaskets.

APPLICATIONS

- Leak-resistant seal for gaskets.
- Heat conductive filling agent helps to dissipate heat and improves transfer of heat.
- Adhesive film holds the gasket in place.
- Convenient cure time allows for repositioning of the gasket if necessary.

DIRECTIONS FOR USE

- 1) Shake well before use, ensuring agitator balls move freely inside the can.
- 2) Spray both sides of the gasket evenly from a distance of ± 20 cm, then place into position.
- 3) A strong tack will develop, holding the gasket in position during tightening. NB: The product will remain tacky for some time and so repositioning of the gasket is possible if necessary.

PROPERTIES

Appearance:	Gold Liquid.
Features:	<ul style="list-style-type: none"> • Specific gravity @25°C: 1.04 • Convenient drying time of the resin allows time for positioning the gaskets. • Flexibility helps removal and re-use of the sealer when used with steel gaskets. • Temperature conduction of copper helps to dissipate high temperatures.

PACKAGING

400 ml aerosol



Revision: draftv3

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Listed Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

