

## ENGINE FLUSH

**Spanjaard Engine Flush** ensures a clean engine before re-filling with new oil. Cleans by dissolving sludge, varnish and carbon deposits. An optimal blend of additives that treats up to 5 litres engine oil capacity in petrol and diesel engines.

### APPLICATIONS

- Used before a scheduled oil change to ensure a clean engine before adding new oil.
- For all engine oil types, synthetic and mineral grades.
- Suitable for petrol and diesel engines.
- Not recommended for use in high mileage engines never previously flushed. Dissolving long-standing deposits can lead to increased clearances and potentially additional oil consumption.

### DIRECTIONS FOR USE

- 1) Engine must be at normal operating temperature.
- 2) Switch engine off then add contents of a full bottle to the old engine oil.
- 3) Run engine at fast idle for 15 min. Do not drive.
- 4) Switch engine off then drain the engine oil.
- 5) Replace oil filter/s.
- 6) Fill with new oil.

### PROPERTIES

<b>Appearance:</b>	Brown/amber transparent liquid
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Fuel economy is improved when an engine is clean.</li> <li>• Exhaust emissions are reduced when a clean engine is well lubricated with new oil.</li> </ul>

### PACKAGING

375 ml	bottle
5 L	tin
20 L	drum



Revision: 311023

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

