

## RED INSULATING VARNISH

Spanjaard Red Insulating Varnish is a fast drying dielectric coating and insulating medium.

### APPLICATIONS

- For use on all electrical windings, coils and motor frames.
- Protects against arcing from controller shafts, switch bases and other electrical equipment.

### DIRECTIONS FOR USE

- 1) Thoroughly degrease components, preferably with a safety solvent.
- 2) Shake can well. From a distance of around 25cm apply 1 or more thin even layers, until desired coating thickness is achieved. Allow a drying time of 3 minutes between coats
- 3) After use, invert can and spray for 3 seconds to clean the nozzle.

### PROPERTIES

Appearance:	Brick Red liquid	
Features:	<ul style="list-style-type: none"> <li>• Di-electric Strength , 25°C (IEC 156): 67-74 KV/mm</li> <li>• Di-electric constant, 25°C: (ASTM D150): 2.9-3.4</li> <li>• Surface resistivity, 25°C (ASTM D257): <math>1 \times 10^{14}</math> ohms/cm<sup>2</sup></li> <li>• Moisture and oil resistant</li> </ul>	

### PACKAGING

- 350 ml      aerosol  
 5lt          tin (for application by airless spray)



Revision: 240124

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

