

SILICONE SPRAY

Spanjaard Silicone Spray is a silicone lubricant and protector. Enhances and renews lustre on rubbers and plastics. Prevents adhesion of weld spatter. Mould release agent in manufacturing. NSF registered for incidental food contact (Category H1: Reg # 139905).

APPLICATIONS

- Renews lustre of sun-faded car bumpers/trim and tyre sidewalls.
- Reliable mould release agent for manufacturing of plastics and rubber.
- Excellent non-staining, non-friction and squeak free properties for rails, hinges, locks, zippers, fishing and sports equipment.
- Safe lubricant for food factory equipment where incidental food contact may occur.
- Spatter release agent for welding.
- Minimal thermal and electrical conductivity.
- Suitable for use in a wide range of temperature conditions.

DIRECTIONS FOR USE

Shake well before use. Spray liberally onto area to be treated. Wipe off excess with a cloth.

PROPERTIES

Appearance	Transparent & colourless
Viscosity (25°C)	500 cSt
Flash point	315 °C
Pour point	-50 °C
Density (25 °C)	0.97 g/ml
Thermal conductivity (25 °C)	0.15 W/(m.K)
Volatility (230 °C for 2h)	< 2 %
Dielectric constant (25°C, 100Hz)	2.7
Surface tension	21.1 mN/m
Operating temp.	-40 to 200 °C

PACKAGING

- 200 ml aerosol
- 400 ml aerosol



Revision: 011123

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

