

SMOKE DOCTOR

Spanjaard Smoke Doctor is an engine oil additive that reduces exhaust smoke caused by oil consumption in worn engines. Improves the viscosity of engine oils when high temperatures are reached. Compatible with mineral and synthetic oils.

APPLICATIONS

- Improves lubrication by reducing friction between metal parts.
- Cushions regular-impact areas such as tappets, cams and gears.
- Maintains fluidity of oil at low temperatures and viscosity of oil at high temperatures.
- For use in petrol and diesel engines.

DIRECTIONS FOR USE

Change engine oil if required. Run the engine until normal operating temperature is reached. Add contents to the engine oil. Run engine for a further 5 minutes to ensure even distribution.

PROPERTIES

Appearance:	Viscous fluid.
Features:	<ul style="list-style-type: none"> • Viscosity at 100°C: 1100 cSt. • Flash point: 200°C. • Pour point: 2°C. • Resistant to low temperature gelation. • Globally compatible with all industry-standard synthetic and mineral engine oils. • Minimises change in engine oil viscosity when subject to temperature variations.

PACKAGING

500 ml bottle
20 L drum



Revision: 030823

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

