TECHNICAL DATA SHEET

TYRE FIX

Spanjaard Tyre Fix repairs and inflates tubed and tubeless tyres without needing a wheel change. A propellant and rubber latex emulsion which inflates then seals small holes in conventional and radial tyres.

APPLICATIONS

- Puncture repair kit for emergency repair of tyres.
- Useful in remote areas.
- Seals punctures by repairing from the inside.
- Not designed for long term use.
- Not suitable for large holes, rim leaks, tyre-side wall damage or faulty valves.

DIRECTIONS FOR USE

- 1) Remove object causing puncture and deflate tyre completely.
- 2) Shake can well. If can is cold, warm in hands for at least 2 minutes.
- 3) Screw connector tube firmly onto tyre valve.
- 4) Break protective tab, hold can upright and depress actuator until can is empty. Disconnect from tyre valve. At this stage tyre may not be fully inflated, which is normal. Drive off immediately, continue for a few kilometres to effect puncture seal. Then stop driving to check and correct tyre pressure.
- 5) Travel at reduced speed (not more than 80 km/h or 50 mph) and have the damaged tyre seen to as soon as possible.

NB: This is a temporary solution.

PACKAGING

340 ml aerosol 600 ml aerosol



Revision: 110523

© Spanjaard (Pty) Ltd

For safety and storage information, please refer to the safety data sheet (SDS).



